



**NOTES:**

1. LEAK TEST: 80 PSI, NO BUBBLES 2 MINUTES MINIMUM. A GREEN PAINT DOT INDICATES PART HAS PASSED THE TEST.
2. QUALIFICATION ONLY:  
LEAK TEST: 340 PSI, NO BUBBLES 1 MINUTE MINIMUM.
3. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
7. VOIDS LARGER THAN  $\phi .035$  [.89] ARE NOT ACCEPTABLE.
8. REF-OPERATING TEMPERATURE -20°C TO 200°C.
9. DIMENSIONS ARE INCHES [millimeters].
10. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

6	A/R	PAVE-Seal 200	EPOXY BLACK
5	1	EE22 UL1180 BLU	WIRE 22EE UL1180 7/#30 BLUE
4	1	EE22 UL1180 WHT	WIRE 22EE UL1180 MARKED 7/#30
3	1	EE22 UL1180 RED	WIRE 22EE UL1180 MARKED 7/#30
2	1	EE22 UL1180 BLK	WIRE 22EE UL1180 MARKED 7/#30
1	1	3383	HOUSING PT8TF-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION  
PT8TF-SS-200-4-TEE22-24-2

PART NUMBER  
**3373**

MATERIAL NOTED

REVISION LEVEL  
D

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS