



NOTES:

1. SEE PAVE DRAWINGS 5833, 5834, & 5835 FOR INDIVIDUAL ASSEMBLY AND COMPONENT DETAILS.
2. REF-OPERATING TEMPERATURE RANGE -20°C TO 85°C.
3. DIMENSIONS ARE INCHES [millimeters].
4. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

3	1	5835	CABLE ASSEMBLY 6 WAY .1P SIL FEMALE TO M8 FEMALE
2	1	5834	CABLE ASSEMBLY USB TYPE A FEMALE W/FT232R TO M8 FEMALE
1	1	5833	VS9-SS-150-6-24-M8M-M8M
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
ASSEMBLY FEEDTHRU VS9M8M TTL-232R-3V3

PART NUMBER 5855	MATERIAL NOTED
REVISION LEVEL A	PROJECTION